

BALL VALVE

BRONZE TWO PIECE, FULL BORE, PN25

Model Number: MV10-11228



FEATURES / CHARACTERSTICS

Rating PN25

Connections BS EN 10226-2

Taper Threaded (ex BS21)

Working Medium Water, Oil and Steam

Two Piece Body, Full Bore Chrome Plated Ball Blow Out Proof Stem , PTFE Seats and Stem Seals

ON REQUEST

NPT Threads, (subject to minimum order quantities)

HYDROSTATIC TEST PRESSURE

Clastic O.7. E. la ave

Shell- 37.5 bar Seat- 27.5 bar

WORKING TEMPERATURE

25 Bar -10° C to 110° C water WRAS approved -10° C to 85° C

MATERIAL SPECIFICATIONS

MATERIAL SI ECITICATIONS					
PARTS	MATERIAL				
Seat Retainer	Bronze CC491K				
Gasket	PTFE				
Seat	PTFE				
Ball	Brass CW614N				
Body	Bronze CC491K				
Stem	Brass CW614N				
Stem Gasket	PTFE				
Packing	PTFE				
Gland Nut	Brass CW614N				
Lever	Mild Steel				
Lever Cover	PVC				
Gasket	Steel				
Lever Nut	Brass CW614N				
	PARTS Seat Retainer Gasket Seat Ball Body Stem Stem Gasket Packing Gland Nut Lever Lever Cover Gasket				

DIMENSIONS (mm)

Sizes		ام			ш
DN	inch	d	L	L1	Н
15	1/2''	14	53	95	44
20	3/4''	19	61	110	51
25	1"	24	71	110	55
32	11/4''	31	85	140	65
40	1½"	38	92	140	70
50	2"	49	114	160	83

^{*}All dimensions are nominal (indicative) Actual dimensions may vary

