



CHECK VALVE

BRASS LIFT CHECK VALVE, PN10

Model Number: **MV30-1407**

FEATURES / CHARACTERISTICS

Rating	PN10
Connection	BS EN 10226-2 Taper Threaded(ex BS21)
Working Medium	Water, Oil and Steam.

Brass Body Lift Pattern,
Threaded Ends

ON REQUEST

NPT Threads (subject to minimum order quantities)

HYDROSTATIC TEST PRESSURE

Shell- 15 bar

Seat- 11 bar

WORKING TEMPERATURE

10 Bar -10° C to 110° C water

MATERIAL SPECIFICATIONS

	PARTS	MATERIAL
1	Body	Brass CW617N
2	Bonnet	Brass CW617N
3	Disc	Brass CW617N
4	Stem	Brass CW617N
5	Rubber	Nitrile Rubber
6	Spring	Stainless Steel 304

DIMENSIONS (mm)

DN	inch	A	L
15	1/2"	33	48
20	3/4"	41	52
25	1"	46	56
32	1 1/4"	56	64
40	1 1/2"	64	72
50	2"	81	76
65	2 1/2"	97	97
80	3"	111	98
100	4"	140	110

*All dimensions are nominal (indicative)
Actual dimensions may vary

