



FLEXIBLE CONNECTOR

FLANGED STAINLESS STEEL WITH CONTROL RODS, PN16

Model Number: **MV600-8.CR**

FEATURES / CHARACTERISTICS

Rating	PN16
Connection	Flanged to BS EN1092-2, PN16 (ex BS4504)
Working Medium	Water, Oil and Steam

Stainless Steel Braided, Stainless Steel Bellow,
Carbon Steel Flanges with Control Rods



ON REQUEST

Other PN Ratings ,Other Body Material (NBR, Viton, etc.)
Hot Dip Galvanized(Tie Rods) (subject to minimum order quantities)

HYDROSTATIC TEST PRESSURE

Shell- 24 bar

WORKING TEMPERATURE

16 Bar -10° C to 100° C water

MATERIAL SPECIFICATIONS

	PARTS	MATERIAL
1	Flange	Carbon Steel
2	Wrapped Circle	Carbon Steel
3	Bellow	SS304
4.	Braid	SS304
5.	Lug Ring	Carbon Steel
6.	Tie Rods	Carbon Steel/(HDG)
7.	Nuts	Carbon Steel/(HDG)

DIMENSIONS (mm)

Sizes		L	D	K	d	n-Øh
DN	inch					
65	2½"	229	185	145	122	4-Ø19
80	3"	229	200	160	138	8-Ø19
100	4"	229	220	180	158	8-Ø19
150	6"	279	285	240	212	8-Ø23
200	8"	305	340	295	268	12-Ø23
250	10"	330	405	355	320	12-Ø28
300	12"	356	460	410	378	12-Ø28
400	16"	356	580	525	490	16-Ø31

*All dimensions are nominal (indicative)
Actual dimensions may vary

