

BRONZE Y-STRAINER, PN20 Model Number: MV70-116



FEATURES / CHARACTERSTICS

Rating Connections

PN20 BS EN 10226-2 Taper Threaded (ex BS21) Working Medium Water, Oil and Steam

Stainless Steel Screen, Screwed Cap

ON REQUEST

NPT Threads, (subject to minimum order quantities)

HYDROSTATIC TEST PRESSURE

Shell- 30 bar

WORKING TEMPERATURE

20 Bar - 10° C to 110° C water WRAS approved -10° C to 85° C

MATERIAL SPECIFICATIONS

SR.	PARTS	MATERIAL	
1	Body	Bronze CC491K	
2	Screen	Stainless Steel 304	
3	Gasket	Bronze CC491K	
4	Сар	PTFE	
5	Plate	Aluminum	

DIMENSIONS (mm)

Sizes				Diameter	Meshes
DN	inch	L	Н	of Hole	/cm²
15	1⁄2"	58	40	0.7	60
20	3⁄4"	70	51	0.7	60
25	1"	88	58	0.7	60
32	11⁄4"	96	69	1.4	28
40	11⁄2"	107	74	1.4	28
50	2"	126	95	1.4	28

5 3 ₽ т L

*All dimensions are nominal (indicative) Actual dimensions may vary

