



STRAINER

DUCTILE IRON Y-STRAINER, PN25
Model Number: MV70-225

FEATURES / CHARACTERISTICS

Design	BS EN558-1 Series 1
Rating	PN25
Connection	Flanged BS EN1092-2, PN25 (ex BS 4504)
Working Medium	Water

Bolted Cover with Drain Plug, Epoxy Coated
 Stainless steel Screen

ON REQUEST

ANSI standards (subject to minimum order quantities).

HYDROSTATIC TEST PRESSURE

Shell- 37.5 bar

WORKING TEMPERATURE

25 Bar -10° C to 110° C water

MATERIAL SPECIFICATIONS

SR.	PARTS	MATERIAL
1	Body	Ductile Iron
2	Cover	Ductile Iron
3	Screen	Stainless Steel
4	Drain Plug	Stainless Steel

DIMENSIONS (mm)

Sizes		L	H	Hole Dia.
DN	inch			
65	2 ½"	290	180	1.5
80	3"	310	215	1.5
100	4"	350	235	1.5
125	5"	400	275	1.5
150	6"	480	305	1.5
200	8"	600	390	2.5
250	10"	730	540	2.5
300	12"	850	680	2.5
350	14"	980	740	2.5
400	16"	1100	845	3.5
450	18"	1200	838	3.5
500	20"	1250	908	3.5
600	24"	1450	1078	3.5

*All dimensions are nominal (indicative)
 Actual dimensions may vary

